# **SAFETY DATA SHEET Water-based Nail Polish**

#### SECTION 1-IDENTIFICATION

**Product Type:** 

Product Identifier: Nail Polish, Colorcoat
Manufacturer: Mad River Science
2736 Clay Road
Makinlawillo, CA 95516

Mckinleyville, CA 95519 Waterborne Nail Polish

Chemical Name: Emulsion resin/pigment mixture

Chemical Family: Water-based paint
CAS No: Mixture/Not Hazardous

# SECTION 2 - HAZARDOUS INGREDIENTS.

The major components of this product are not hazardous. Those several minor components which would normally present a nuisance under certain conditions of massive exposures are present in this product in very small amounts.

## **SECTION 3 - COMPOSITION**

	CAS	INCI Name	Color Index	Maximum %
Components	Number		Number	<u>weight</u>
Water	7732-18-5	Aqua		49.42
Acrylates copolymer	mixture	Acrylates copolymen	r	38.18
Methyldipropasol	34590-94-8	PPG-2-Methyl Ethe	er	4.08
Ethanol	64-17-5	Alcohol		4.08
Texanol	25265-77-4	Trimethyl Hydroxybutyl Isobutyrate		2.04
Laponite RDS	258-476-2	Sodium Magnesium Silicate		1.62
EO Urethane copolymer	· mixture	Urethane copolymer		0.58
D&C Red 7, Ca Lake	5281-04-9	Red 7	15850:1	(8.70)
D&C Red 34, Ca Lake	6417-83-0	Red 34	6417-83-0	(4.73)
D&C Red 28	13473-26-2	Red 28	45410	(2.40)
D&C Red 17	85-86-9	Red 17	26100	(1.59)
Pur Oxy Black	12227-89-3	Iron oxide	77499	(2.40)
Titanium Dioxide	13463-67-7	Titanium dioxide	77891	(0.90)
Ultramarine Blue	57455-37-5	Ultramarines	77007	(0.53)
Chromium Hydroxide	1308-14-1	Chrome Green	77289	(0.09)
Mica	12001-26-2	Mica	77019	(1.92)
D&C Violet 2	4430-18-6	Violet 2	60730	(3.98)

## **SECTION 4 – FIRST AID MEASURES**

**Eye Contact**: Flush eyes with large amounts of running water until water runs clear. Consult a doctor immediately.

**Skin Contact**: Wash with soap and water. Remove and wash contaminated clothing. Consult a doctor if irritation develops.

**Inhalation**: If vapor or mist is inhaled, remove to fresh air. Treat symptoms of irritation if necessary.

**Ingestion**: No harmful effect is anticipated. Intensely bitter. However, if a large amount (several ounces, 8 to 10 bottles) is swallowed, it is advisable to induce vomiting. Consult a doctor. Note to physician: Glycol ethers can cause delayed liver and kidney damage. Careful evacuation of the stomach is advisable.

## **SECTION 5- FIRE-FIGHTING MEASURES**

**Extinguishing Agents**: This product is not a fire hazard as supplied since it contains no flammable materials. After water has evaporated, however, the remaining solids could ignite.

Use water spray or general purpose foams for large fires, dry chemical or CO2 for small fires.

Special fire Fighting Precautions: Wear self-contained breathing apparatus when fighting fires in enclosed areas or when exposure to smoke and gases could occur (including cleanup\salvage operations). Unusual Fire and Explosion Hazards: Product may spatter if temperature of liquid exceeds the boiling point of water. If solids ignite, toxic and irritating gases will be emitted.

## SECTION 6- ACCIDENTAL RELEASE MEASURES

Don over-alls to protect clothes from splatters. Contain spill and recover as much as possible for reuse. Collect remainder with absorbents and place in a closed container to await disposal. If spill is in an enclosed space, provide ventilation. Spilled product is very slippery. Use caution to avoid falls. Clean spill area thoroughly with soap and water before product dries. Equipment or personal property should be washed before product dries to minimize damage. Consult with the local sewer or water pollution agencies before discharging to a sewer or waterway.

## **SECTION 7 – HANDLING AND STORAGE**

**Normal Processing:** Suitable controls should be used to control process emissions. Employees should wash before eating or smoking. If clothing or shoes become contaminated, wash before reuse.

**Storage:** Store at temperatures between 50-100 deg F. Do not allow to freeze.

Minimize contact with air to reduce contamination with mold, fungus and other organisms which could cause decomposition or spoilage.

## SECTION 8 – EXPOSURE CONTROLS/PERSONAL PROTECTION

Hazard Codes:			
NFPA 704 (*)	:	HMIS(**):	
Health	1	Health	1
Flammability	0	Flammability	0
Reactivity	0	Reactivity	0

Special None Personal Protection B(Gloves, goggles)

\* NFPA=National Fire Protection Association hazard rating system based on severity of hazard under fire conditions.

\*\* HMIS=Hazardous Materials Identification System based on National Paint and Coatings Association criteria for the product as delivered..

**Ventilation:** Use local exhaust ventilation to control mists or vapors generated if product is spray-applied. Ventilation must keep exposures below regulated limits.

**Respiratory Protection:** None normally required. If exposures are anticipated to be excessive, appropriate respirators should be selected by a qualified individual.

**Eye Protection:** Safety glasses. Use chemical safety goggles if splashing could occur.

**Special Protective Equipment:** Gloves suitable for use in water and chemically resistant should be worn when contact is expected.

# SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

This product is a water-based paint with a mild, acrylic odor and clear, liquid appearance in the absence of colorants. Its boiling point is slightly greater than 212 deg F, pH is slightly alkaline (7.5-8.5), and it is readily diluted with water. Solids content is approximately 25 percent.

#### SECTION 10 – STABILITY AND REACTIVITY

Auto-ignition Temperature - Not Applicable Lower Explosive Limit- Not Applicable

**Upper Explosive Limit** - Not Applicable

**EPA/DOT Reportable Quantity** – Not Applicable

**DOT Labels**: None Required

**Instability**: This material is considered stable. However, avoid temperatures above 177 deg C (350 deg F), the onset of polymer decomposition. Thermal decomposition is dependent on time and temperature.

**Hazardous Decomposition Products**: CO, CO2, HCN, oxides of nitrogen and small amounts of aromatic or aliphatic hydrocarbons can be generated from combustion of dry or cured latex.

Hazardous Polymerization: This product will not undergo polymerization.

**Incompatibility**: Avoid contact with acids, alkalies and strong oxidizing agents.

#### SECTION 11 - TOXICOLOGICAL INFORMATION

**Primary Routes of Exposure**: Eye/skin contact. Inhalation

**Conditions Aggravated by Exposure:** None specific to product. Individuals with sensitive airways (e.g. asthmatics) may react to airborne vapors. Persons with pre-existing skin problems or latex-glove allergies may be aggravated by contact with this product in liquid form.

**Effects of Overexposure**. Vapors or direct eye contact may cause irritation. Acute overexposure to vapors as may occur when heated or burned may cause nausea, dizziness or flu-like symptoms. Accidental ingestion may cause discomfort in the throat and stomach.

## **SECTION 12 – ECOLOGICAL INFORMATION**

All components of this product are biodegradable. Dilution of run-off from large spills with copious amounts of water will mitigate the threat to waterways and wildlife.

## SECTION 13- DISPOSAL CONSIDERATION

This product is not considered a Hazardous Waste under current Federal RCRA requirements. Liquid product should not be disposed in a landfill. Liquid product generally requires some pre-disposal treatment to separate the liquid portion from polymer and pigments. This is typically done by coagulating the polymer and solids with alum and removing the liquid. The liquid portion is discharged to an appropriate industrial or public treatment works (with approval of appropriate authority) Solids should be sent to an approved landfill or preferably, incinerated. Product as a whole can be incin erated in suitable equipment.

## **SECTION 14 – TRANSPORT INFORMATION**

**DOT Proper Shipping Name**: Not Regulated **DOT Primary Hazard Classification**: NA

UN/NA Hazard No.: NE Flash Point: noncombustible

# **SECTION 15 – REGULATORY INFORMATION**

Not applicable..

## **SECTION 16- OTHER INFORMATION**

**Date of Preparation**: September 9, 2021

**User's Responsibility:** This bulletin cannot cover all possible situations which the user may experience during processing. Each aspect of user's operation must be examined to determine if, when and where, additional precautions may be necessary. All health and safety information contained in this bulletin must be provided to your employees or customers. It is your responsibility to use this information to develop appropriate work practice guidelines and employee instructional programs for your operation.

**Disclaimer of Liability:** As the conditions or methods of use are beyond our control, we do not assume any responsibility and expressly disclaim any liability for any use of this material. Information contained herein is believed to be true and accurate but all statements or suggestions are made without warranty, express or implied, regarding accuracy of the information, the hazards connected with the use of the material or the results to be obtained from the use thereof. Compliance with all applicable federal, state and local laws and regulations remains the responsibility of the user.